







TRAVI

TRAVI "INP" SERIE NORMALE



DESIGNAZIONE	PESO KG/M	SUP. M ² /T	SEZ. CMC	DIMENSIONI				
				H mm	B mm	A mm	E mm	R mm
80	5,95	51,18	7,58	80	42	3,9	5,76	3,9
100	8,32	44,36	10,6	100	50	4,5	6,64	4,5
120	11,20	39,55	14,2	120	58	5,1	7,52	5,1
140	14,40	35,10	18,3	140	66	5,7	8,40	5,7
160	17,90	32,12	22,8	160	74	6,3	9,28	6,3
180	21,9	29,22	27,9	180	82	6,9	10,16	6,9
200	26,3	27,06	33,5	200	90	7,5	11,04	7,5
220	31,1	24,92	39,6	220	98	8,1	11,92	8,1
240	36,2	23,31	46,1	240	106	8,7	12,80	8,7
260	41,9	21,62	53,4	260	113	9,4	13,77	9,4
280	48,0	20,17	61,1	280	119	10,1	14,85	10,1
300	54,2	19,00	69,1	300	125	10,8	15,82	10,8
320	61,1	17,87	77,8	320	131	11,5	16,90	11,5
340	68,1	16,91	86,8	340	137	12,2	17,87	12,2
360	76,2	15,90	97,1	360	143	13,0	19,05	13,0
380	84,0	15,12	107,0	380	149	13,7	20,02	13,7
400	92,6	14,39	118,0	400	155	14,4	21,10	14,4
450	115	12,87	147	450	170	16,2	24,3	6,2
500	141	11,56	180	500	185	18,0	27,0	18,0


TRAVI "IPE" AD ALI PARALLELE



DESIGNAZIONE	PESO KG/M	SUP. M ² /T	SEZ. CMQ	DIMENSIONI				
				H mm	B mm	A mm	E mm	R mm
80	6,00	54,67	7,64	80	46	3,8	5,2	5
100	8,10	49,38	10,3	100	55	4,1	5,7	7
120	10,4	45,67	13,2	120	64	4,4	6,3	7
140	12,9	42,71	16,4	140	73	4,7	6,9	7
160	15,8	39,43	20,1	160	82	5,0	7,4	9
180	18,8	37,13	23,9	180	91	5,3	8,0	9
200	22,4	34,29	28,5	200	100	5,6	8,5	12
220	26,2	32,37	33,4	220	110	5,9	9,2	12
240	30,7	30,03	39,1	240	120	6,2	9,8	15
270	36,1	28,81	45,9	270	135	6,6	10,2	15
300	42,2	27,49	53,8	300	150	7,1	10,7	15
330	49,1	25,46	62,6	330	160	7,5	11,5	18
360	57,1	23,64	72,7	360	170	8,0	12,7	18
400	66,3	22,17	84,5	400	180	8,6	13,5	21
450	77,6	20,75	98,8	450	190	9,4	14,6	21
500	90,7	19,18	116	500	200	10,2	16,0	21
550	106	17,74	134	550	210	11,1	17,2	24
600	122	16,48	156	600	220	12,0	19,0	24

TRAVI "HEA" AD ALI LARGHE E PARALLELE


Serie leggera



DESIGNAZIONE	PESO KG/M	SUP. M ² /T	SEZ. CMC	DIMENSIONI				
				H mm	B mm	A mm	E mm	R mm
100	16,7	33,59	21,2	96	100	5	8	12
120	19,9	34,02	25,3	114	120	5	8	12
140	24,7	32,15	31,4	133	140	5,5	8,5	12
160	30,4	29,80	38,8	152	160	6	9	15
180	35,5	28,73	45,3	171	180	6	9,5	15
200	42,3	26,95	53,8	190	200	6,5	10	18
220	50,5	24,95	64,3	210	220	7	11	18
240	60,3	22,72	76,8	230	240	7,5	12	21
260	68,2	21,70	86,8	250	260	7,5	12,5	24
280	76,4	20,94	97,3	270	280	8	13	24
300	88,3	19,48	113	290	300	8,5	14	27
320	97,6	18,03	124	310	300	9	15,5	27
340	105	17,05	133	330	300	9,5	16,5	27
360	112	16,34	143	350	300	10	17,5	27
400	125	15,28	159	390	300	11	19	27
450	140	14,36	178	440	300	11,5	21	27
500	155	13,61	198	490	300	12	23	27
550	166	13,31	212	540	300	12,5	24	27
600	178	12,98	226	590	300	13	25	27
650	190	12,68	242	640	300	13,5	26	27
700	204	12,25	260	690	300	14,5	27	27
800	224	12,05	286	790	300	15	28	30
900	252	11,51	321	890	300	16	30	30
1000	272	11,40	347	990	300	16,5	31	30

TRAVI "HEB" AD ALI LARGHE E PARALLELE

Serie normale




TRAVI

DESIGNAZIONE	PESO KG/M	SUP. M ² /T	SEZ. CMQ	DIMENSIONI				
				H mm	B mm	A mm	E mm	R mm
100	20,4	27,79	26,0	100	100	6	10	12
120	26,7	25,69	34,0	120	120	6,5	11	12
140	33,7	23,89	43,0	140	140	7	12	12
160	42,6	21,55	54,3	160	160	8	13	15
180	51,2	20,31	65,3	180	180	8,5	14	15
200	61,3	18,76	78,1	200	200	9	15	18
220	71,5	17,76	91,0	220	220	9,5	16	18
240	83,2	16,59	106	240	240	10	17	21
260	93,0	16,13	118	260	260	10	17,5	24
280	103	15,73	131	280	280	10,5	18	24
300	117	14,79	149	300	300	11	19	27
320	127	13,94	161	320	300	11,5	20,5	27
340	134	13,51	171	340	300	12	21,5	27
360	142	13,03	181	360	300	12,5	22,5	27
400	155	12,45	198	400	300	13,5	24	27
450	171	11,87	218	450	300	14	26	27
500	187	11,34	239	500	300	14,5	28	27
550	199	11,16	254	550	300	15	29	27
600	212	10,94	270	600	300	15,5	30	27
650	225	10,76	286	650	300	16	31	27
700	241	10,46	306	700	300	17	32	27
800	262	10,34	334	800	300	17,5	33	30
900	291	10,00	371	900	300	18,5	35	30
1000	314	9,90	400	1000	300	19	36	30

TRAVI "HEM" AD ALI LARGHE E PARALLELE

Serie rinforzata



DESIGNAZIONE	PESO KG/M	SUP. M ² /T	SEZ. CMQ	DIMENSIONI				
				H MM	B MM	A MM	E MM	R MM
100	41,8	14,81	53,2	120	106	12	20	12
120	52,1	14,17	66,4	140	126	12,5	21	12
140	63,2	13,56	80,6	160	146	13	22	12
160	76,2	12,73	97,1	180	166	14	23	15
180	88,9	12,26	113	200	186	14,5	24	15
200	103	11,65	131	220	206	15	25	18
220	117	11,28	149	240	226	15,5	26	18
240	157	9,23	200	270	248	18	32	21
260	172	9,13	220	290	268	18	32,5	24
280	189	8,94	240	310	288	18,5	33	24
300	238	7,69	303	340	310	21	39	27
320	245	7,63	312	359	309	21	40	27
340	248	7,66	316	377	309	21	40	27
360	250	7,72	319	395	308	21	40	27
400	256	7,81	326	432	307	21	40	27
450	263	7,98	335	478	307	21	40	27
500	270	8,07	344	524	306	21	40	27
550	278	8,20	354	572	306	21	40	27
600	285	8,32	364	620	305	21	40	27
650	293	8,43	374	668	305	21	40	27
700	301	8,50	383	716	304	21	40	27
800	317	8,68	404	814	303	21	40	30
900	333	8,80	424	910	302	21	40	30
1000	349	8,97	444	1008	302	21	40	30

LAVORAZIONI

/ LAVORAZIONI AL LASER

/ TAGLIO A MISURA

/ FORATURA

/ FILETTI

/ ASOLE

/ TASCHE

/ MARCATURE

/ SCANTONATURE

Tabella tagli inclinati

